

FEATURES

- Fire Retardant Blue SMS Coveralls
(Spunbond-Meltblown-Spunbond), Hood, Elastic Wrists and Ankles
- 3 Layer Blue FR SMS Nonwoven Polypropylene
- High Breathability and Excellent Comfort
- Effective Protection against Hazardous Dry Particles and Light Liquid Sprays
- Single-Use Flame Resistant Protective Clothing for Use Over Primary Flame Resistant Protective Clothing
- Sizes: S - 5XL , Case Pack: 25 Pieces



APPLICATIONS

Oil Refinery, Welding, Energy, Cleanroom,
Asbestos Hazard Clean Up Utilities,
Construction, General Maintenance,
Painting, Drywall, Chemical, Manufacturing

TECHNICAL DATA

PROPERTY	TEST METHOD	TYPICAL RESULT
Vertical Flame Resistance	ASTM D6413	<8 Inches Char Damage
Vertical Flame Resistance	ASTM D6413	< 2 Seconds After Flame
Protection Against Flame	EN14116-2015	Pass
Weight Loss & Drip Burn	NFPA 701-2019	Pass

DIMENSIONS

SIZE(IN)	SLEEVE LENGTH	CHEST WIDTH	INSEAM	FITS CHEST	FITS HEIGHT	BOOT LENGTH
S	33 1/2	23 1/2	28	33 1/4 - 38 3/4	5'1" - 5'4"	12 1/4
M	34	25 1/4	28 1/2	36 1/4 - 40 3/4	5'4" - 5'8"	12 1/4
L	35	26 1/2	29	39 3/4 - 43 1/4	5'5" - 5'9"	14 1/2
XL	36 1/2	28	29 1/2	42 3/4 - 46 1/4	5'8" - 6'2"	14 1/2
2XL	38	29 1/4	30 1/2	45 1/4 - 48 3/4	6'0" - 6'4"	16 1/4
3XL	38	31 1/4	31 1/2	49 1/4 - 52 3/4	6'2" - 6'4"	16 1/4
4XL	38 1/2	33	32 1/2	52 3/4 - 56 1/4	6'4" - 6'7"	16 1/4
5XL	39 1/2	34 1/2	33 1/2	55 3/4 - 59 1/4	6'7" - 6'10"	16 1/4

*Tolerance of measurement \pm 5%